


ROUGH TOP CONVEYOR BELTS

Transportation or conveying of lightweight materials like cartons, paper, glass, packaged goods etc., on flat or inclined surfaces, requires a special kind of belt.

Having a ridged rubber surface on the top and either a bare back fabric or a regular rubber back, INDUS SUPER RIDGE conveyor belts are specially designed for this purpose. The ridges on the top cover offer a massive friction coefficient to ensure that the material being conveyed doesn't slip or roll back.

INDUSTRY:

- Food Packaging Industry
- Industrial Applications
- Glass & Other Fragile Goods Manufacturing Industry.
- Bagging Plants
- Corrugated Box & Paper Industry



PRODUCT FEATURES

Standard Widths	Up to 1500mm (60")
Type of Fabric	EP / NN
Standard Belt Rating	100 kN/m (57 PIW) to 1000 kN/m (571 PIW)
No. of Ply's	1 Ply to 4 Ply
Rubber Cover Thickness	Top cover: Up to 5 mm (1/5") Bottom cover: Up to 3mm (1/8") Bare Back Surface also available.
Colour	Black
Edge	Cut Edge
Splicing Method	Hot / Mechanical
Cover Grades	Available in General Purpose Impact & Abrasion Resistant (M24, DIN-X, Y, HAR, SAR), Oil Resistant (OR), Heat Resistant (HR), Fire Resistant (FR) grades and combinations available on request.
Single Roll length	200 Meters (650') Longer roll lengths available on request.
Standard Packing	Wrapping in Blue HDPE sheets with Strapping. (Wooden Crate / Metal Crate packing is available on request)
Belt Identification Number	A unique BIN (Belt Identification Number) at every 10 meters (33')

*Specifications are subject to change without notice.

